#### STATE OF MISSOURI

### DEPARTMENT OF NATURAL RESOURCES

MISSOURI AIR CONSERVATION COMMISSION



PERMIT BOOK

### PERMIT TO CONSTRUCT

Under the authority of RSMo 643 and the Federal Clean Air Act the applicant is authorized to construct the air contaminant source(s) described below, in accordance with the laws, rules and conditions as set forth herein.

Permit Number: 042006-001

Project Number:

2005-11-023

037-5001

Owner:

**Materials Packaging Corporation** 

Owner's Address:

P.O. Box B, Harrisonville, MO 64071

Installation Name:

Materials Packaging Corporation

Installation Address:

23018 South 291 Highway, Harrisonville, MO 64071

Location Information:

Cass County, S20, T45N, R31W

Application for Authority to Construct was made for:

The modification of an existing, stationary plant that packages dry mix concrete, aggregate, sand, and salt. The concrete plant has a maximum hourly design rate (MHDR) of 180 tons per hour (tph). This review was conducted in accordance with Section (5), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

☐ Standard Conditions (on reverse) are applicable to this permit.		
Standard Conditions (on reverse) and Special Conditions (listed as attachments starting on pag applicable to this permit.	e 2)	are

**APR 3** 2006

EFFECTIVE DATE

DIRECTOR OR DESIGNEE
DEPARTMENT OF NATURAL RESOURCES

MO 780-1204 (1-03)

#### STANDARD CONDITIONS:

Permission to construct may be revoked if you fail to begin construction or modification within two years from the effective date of this permit. Permittee should notify the Air Pollution Control Program if construction or modification is not started within two years after the effective date of this permit, or if construction or modification is suspended for one year or more.

You will be in violation of 10 CSR 10-6.060 if you fail to adhere to the specifications and conditions listed in your application, this permit and the project review. Specifically, all air contaminant control devices shall be operated and maintained as specified in the application, associated plans and specifications.

You must notify the Air Pollution Control Program of the anticipated date of start up of this (these) air contaminant source(s). The information must be made available not more than 60 days but at least 30 days in advance of this date. Also, you must notify the Department of Natural Resources Regional Office responsible for the area within which you are located within 15 days after the actual start up of this (these) air contaminant source(s).

A copy of this permit and permit review shall be kept at the installation address and shall be made available to Department of Natural Resources' personnel upon request.

You may appeal this permit or any of the listed Special Conditions as provided in RSMo 643.075. If you choose to appeal, the Air Pollution Control Program must receive your written declaration within 30 days of receipt of this permit.

If you choose not to appeal, this certificate, the project review, your application and associated correspondence constitutes your permit to construct. The permit allows you to construct and operate your air contaminant source(s), but in no way relieves you of your obligation to comply with all applicable provisions of the Missouri Air Conservation Law, regulations of the Missouri Department of Natural Resources and other applicable federal, state and local laws and ordinances.

The Department of Natural Resources has established the Outreach and Assistance Center to help in completing future applications or fielding complaints about the permitting process. You are invited to contact them at 1-800-361-4827 or (573) 526-6627, or in writing addressed to Outreach and Assistance Center, P.O. Box 176, Jefferson City, MO 65102-0176.

The Air Pollution Control Program invites your questions regarding this air pollution permit. Please contact the Construction Permit Unit at (573) 751-4817. If you prefer to write, please address your correspondence to the Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102-0176, attention Construction Permit Unit.

2005-11-023 037-5001

Materials Packaging Corporation

P.O. Box B, Harrisonville, MO 64071

Materials Packaging Corporation

23018 South 291 Highway, Harrisonville, MO 64071

Cass County, S20, T45N, R31W

The modification of an existing, stationary plant that packages dry mix concrete, aggregate, sand, and salt. The concrete plant has a maximum hourly design rate (MHDR) of 180 tons per hour (tph). This review was conducted in accordance with Section (5), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

Page No.	2
Permit No.	
Project No.	2005-11-023

#### SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

The special conditions listed in this permit were included based on the authority granted the Missouri Air Pollution Control Program by the Missouri Air Conservation Law (specifically 643.075); by the Missouri Rules listed in Title 10, Division 10 of the Codes of State Regulations (specifically 10 CSR 10-6.060); by 10 CSR 10-6.060 paragraph (12)(A)10. "Conditions required by permitting authority"; by 10 CSR 10-6.010 "Ambient Air Quality Standards" and 10 CSR 10-6.060 subsections (5)(D) and (6)(A); and by control measures requested by the applicant, in their permit application, to reduce the amount of air pollutants being emitted, in accordance with 10 CSR 10-6.060 paragraph (6)(E)3.

#### 1. Best Management Practices

Materials Packaging Corporation shall control fugitive emissions from all of the haul roads and stockpiles at this site by performing *Best Management Practices*, which include the usage of paving, chemical dust suppressants, or documented watering. These practices are defined in Attachment AA.

- 2. National Ambient Air Quality Standards (NAAQS) Limitation for Particulate Matter Less Than Ten Microns in Diameter (PM<sub>10</sub>)
  - A. The operator(s) for Materials Packaging Corporation's concrete plant (037-5001) shall ensure, while operating at this site, that the ambient impact of PM<sub>10</sub> at or beyond the nearest property boundary does not exceed 150 μg/m³ in any 24-hour period, in accordance with the Federal NAAQS requirements (40 CFR 50.6).
  - B. To demonstrate compliance, the operator(s) shall maintain a daily record of material processed. Attachment A, *Daily Ambient PM*<sub>10</sub> *Impact Tracking Record,* or other equivalent form(s), will be used for this purpose.

#### 3. Dust Collector(s) Control System Requirements

A. Materials Packaging Corporation shall install and operate dust collector(s) to restrict the emission of particulate matter. The dust collector(s) must be used whenever these units are in operation. The dust collector(s) shall be installed on the following units: Bag Loading (EU14, EU15, and EU16), Cement Unloading (EU03), Cement Supplement Unloading (EU04), and Weigh Hopper Loading for Cement and Cement Supplement (EU07).

#### B. Monitoring

- (a) Visible emissions will be used as an indicator of the proper operation of the control device. During proper operation no visible emissions are expected from this emission unit. The existence of visible emissions will indicate a decrease in the efficiency of the control device and corrective actions will be implemented. Observations will be made using a USEPA Method 22 trained observer and USEPA Method 22 like procedures.
- (b) Frequency: Visible emissions from the exhaust shall be monitored on a daily basis when the process is in operation.
- (c) Duration: The duration of the observation shall be for a two minute time period.
- (d) Threshold: The condition of no visible emissions is considered normal for this emission unit. When visible emissions are noted from the emission unit, it shall be documented and corrective actions taken.
- (e) The observation of visible emissions from this emission unit will be considered an excursion and corrective actions shall be implemented within a reasonable period. An excursion does not necessarily indicate a violation of the applicable requirement. When the level of excursions exceed three percent of the of the total number of observations in a six month period and corrective actions fail to return the emission unit to a no visible emission condition, then the permittee shall conduct source testing within 90 days of the last excursion to demonstrate compliance with 10 CSR 10-6.400. If the test demonstrates noncompliance with the above emission limitation the permittee shall propose a schedule to implement further corrective actions to bring the source into compliance and demonstrate that compliance.
- (f) All control equipment shall be maintained and operated according to the manufacturer's specifications.

Page No.	3
Permit No.	
Project No.	2005-11-023

#### SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

- 4. Prohibition Against Concurrent Operations Without Further Air Pollution Control Program Review The concrete plant (037-5001) is prohibited from operating whenever any other plant(s) are located at this site.
- 5. Restriction on Minimum Distance to Nearest Property Boundary
  The primary emission point of the concrete plant, which is the Bag Loading (EU14, EU15, and EU16), shall be located at least 130 feet from the nearest property boundary whenever it is operating at this site.
- 6. Record Keeping Requirement

The operator(s) shall maintain all records required by this permit for not less than five (5) years and shall make them available immediately to any Missouri Department of Natural Resources' personnel upon request.

7. Reporting Requirement

The operator(s) shall report to the Air Pollution Control Program Enforcement Section, P.O. Box 176, Jefferson City, MO 65102, no later than ten (10) days after any exceedances of the limitations imposed by this permit.

8. Superseding Condition

The conditions of this permit supersede all special conditions found in the previously issued construction permit(s) (092003-004, 092005-018) from the Air Pollution Control Program.

#### TECHNICAL REVIEW OF APPLICATION FOR AUTHORITY TO CONSTRUCT

#### PROJECT DESCRIPTION

This installation is not on the List of Named Installations [10 CSR 10-6.020(3)(B), Table 2]. The installation is located in Cass County, an attainment area for all criteria air pollutants. This installation blends and packages dry mix concrete (Lines 1-3), and packages sand (Line 4), aggregate (also Line 4), and rock salt (Line 5). No electrical generators are used at this installation; it is powered entirely by electrical line power. Lines 4 and 5 were constructed prior to receipt of a New Source Review permit from the Air Pollution Control Program. Obtaining this permit is part of a remedial action required by the Air Pollution Control Program.

Dry, bagged concrete mix composed of cement, sand, and non-metallic course aggregate rock is produced by mixing and bagging on three lines designated as Lines 1-3. Line 4 processes sand and rock (one or the other at a time), which are transported from front end loaders to hoppers, a conveyor, and a bagging machine. The spreadsheet for this line analyzed aggregate processing only. Sand processing was not included in the spreadsheet because only one material is packaged at a time, and the aggregate emissions and ambient impact are higher than those for packaging sand. Line 5 is used solely for bagging rock salt, and is composed of truck unloading to a conveyor, a hopper, a screw conveyor, a bucket elevator, a weigh hopper, and a bagging machine. Since the MHDR of Lines 4 and 5 are much lower than that of Lines 1-3, separate spreadsheets were generated and separate emission factors were developed for the plant. The record keeping for daily ambient impact (Attachment A) therefore mimics that of concurrently operating plants owned by the same company.

All haul roads and storage pile emissions are accounted for in the spreadsheet for the dry mix concrete packaging except for the following emission: unloading sand and rock from their respective storage piles and dropping these materials into the Load Hopper. Best Management Practices are used to control fugitive emissions from all haul roads and stockpiles.

Cartridge dust collectors are used to control particulate emissions from concrete packaging Lines 1-3. On Line 5, the two conveyors and bucket elevator are enclosed. Lines 4 and 5 are partially contained in a building. Since this building is routinely used by workers and not under constant negative pressure, no control efficiency was given for this enclosure.

Table 1. Other Permits Issued for Site 037-5001

Permit Number	Completed	Description
092003-004	2003	Section 5
092005-018	2005	Section 5

Notice of Violation (NOV) #2211KC was issued for this installation for failure to pave haul roads as specified by New Source Review, Air Pollution Control Program Permit 092003-004 (CFR 6.060).

#### **EMISSIONS EVALUATION**

Criteria air pollutants will be emitted from this operation. The main air pollutant of concern is  $PM_{10}$ . The potential emissions were calculated from the maximum hourly design rate (MHDR) of the equipment, appropriate emission factors, control device efficiencies, and the limiting operating hours at MHDR. The sources of the emission factors and control efficiencies are listed in the section "Permit Documents". Based on the conditioned potential emissions, the operation is considered a *de minimis* source under 10 CSR 10-6.060 section (5).

Table 2: Emissions Summary (tons per year)

		many (some per y	/		
Air Pollutant	Regulatory De Minimis Levels	Existing Actual Emissions (2004 EIQ)	Potential Emissions of the Application	**New Installation Conditioned Potential	Emission Factor (lb/ton)
PM <sub>10</sub>	15.0	0.15	10.2	5.2	N/A
SOx	40.0	N/A	N/A	N/A	N/A
NOx	40.0	N/A	N/A	N/A	N/A
VOC	40.0	N/A	N/A	N/A	N/A
CO	100.0	N/A	N/A	N/A	N/A
HAPs	10.0/25.0	N/A	N/A	N/A	N/A

Note: N/A = Not Applicable

<sup>\*\*</sup> Conditioned potential based on daily production limit from ambient impact analysis.

#### **AMBIENT AIR QUALITY IMPACT ANALYSIS**

Screening tools were used to evaluate the ambient air impact of the hourly emissions from this operation. The ambient impact was evaluated at a distance of 130 feet to the nearest property boundary. The ambient impact at this site shall not exceed the National Ambient Air Quality Standard (NAAQS) of  $150 \,\mu\text{g/m}^3$  of  $PM_{10}$  at or beyond the nearest property boundary in any single 24-hour period. The screening tools were used to develop an ambient impact factor for the concrete plant. This ambient impact factor is incorporated into the daily record keeping table, Attachment A.

For sources agreeing to use Best Management Practices (BMPs), as defined in Attachment AA, haul roads and stockpiles are not modeled with screening tools. Instead, they are addressed as a background level of 20  $\mu$ g/m<sup>3</sup> of PM<sub>10</sub>. To ensure conformity with NAAQS, the remaining process emissions are limited to an impact of less than 130  $\mu$ g/m<sup>3</sup> of PM<sub>10</sub> at or beyond the nearest property boundary.

Table 3: Ambient Air Quality Impact Analysis of PM<sub>10</sub>, 24-Hour Averaging Time

Operation	Ambient Impact Factor (µg/m³ton)	Modeled Impact (μg/m³)	**Background (µg/m³)	NAAQS (μg/m³)	Daily Production Limit (tons)
Solitary	Lines 1-3: 0.0628 Line 4: 0.0656 Line 5: 0.1662	*	20.00	150.00	***

<sup>\*</sup> See Attachment A to calculate the modeled impact based on hours of operation of (1) Lines 1-3, (2) Line 4, and (3) Line 5. See attached spreadsheet summaries for modeled impact when each plant is running solitarily.

#### **APPLICABLE REQUIREMENTS**

The owner is subject to compliance with the following applicable requirements. The Missouri Air Conservation Laws and Regulations should be consulted for specific record keeping, monitoring, and reporting requirements.

- Submission of Emission Data, Emission Fees and Process Information, 10 CSR 10-6.110
- Operating Permits, 10 CSR 10-6.065
- No Operating Permit is required for this concrete plant.
- Restriction of Particulate Matter to the Ambient Air Beyond the Premises of Origin, 10 CSR 10-6.170
- Restriction of Emission of Visible Air Contaminants, 10 CSR 10-6.220
- Restriction of Emission of Odors, 10 CSR 10-3.090
- Restriction of Emission of Particulate Matter From Industrial Processes, 10 CSR 10-6.400
- None of the New Source Performance Standards (NSPS) apply to the proposed equipment.
- The National Emission Standards for Hazardous Air Pollutants (NESHAPs) and the currently promulgated Maximum Achievable Control Technology (MACT) regulations do not apply to the proposed equipment.

#### STAFF RECOMMENDATION

On the basis of this review conducted in accordance with Section (5), Missouri State Rule 10 CSR 10-6.00 Construction Permits Required, I recommend this permit be granted with special conditions.						
Jeannie Kozak Environmental Engineer	Date					

#### PERMIT DOCUMENTS

The following documents are incorporated by reference into this permit:

- The Application for Authority to Construct form, designating Materials Packaging Corporation as the owner and operator of the installation.
- Environmental Protection Agency (EPA) AP-42, Compilation of Air Pollutant Emission Factors; Volume I, Stationary Point and Area Sources, Fifth Edition.
- Noyes Data Corp., Orlemann, et al.1983, Fugitive Dust Control.
- EPA Factor Information Retrieval (FIRE) Version 6.21.
- Spreadsheet calculations of potential-to-emit and ambient impact.
- Kansas City Regional Office Site Survey.
- Best Management Practices

<sup>\*\*</sup> Background PM<sub>10</sub> level of 20.00 μg/m<sup>3</sup> from haul roads and stockpiles.

<sup>\*\*\*</sup> The operator(s) must balance production among Lines 1-3, Line 4 and Line 5, with the ambient impact factors for each, such that NAAQS is not exceeded.

## Attachment A: Daily Ambient PM<sub>10</sub> Impact Tracking Record Materials Packaging Corporation, 037-5001 – Concrete Plant

Project Number: 2005-11-023

County, CSTR: Cass County (S20, T45N, R31W)

Primary Unit Size: 180 tph

Distance to Nearest Property Boundary: 130 feet

This sheet covers the period from \_\_\_\_\_ to \_\_\_\_ to \_\_\_\_ (Month, Day, Year) (Copy this sheet as needed.)

				Materials Packaging Corporation Materials Pac 037-5001 Materials Pac 037-5001			e 5: Rock Salt erials Packaging Corporation -5001 ect # 2005-11-023				
	D - 15 -	Ambient	1D-11- DM	D-35	Ambient	1D - 11 - DM	D-3b	Ambient	1D - 1 - DM	<sup>2</sup> Back-	270741
	Daily Production	Impact Factor	<sup>1</sup> Daily PM <sub>10</sub> Impact	Daily Production	Impact Factor	<sup>1</sup> Daily PM <sub>10</sub> Impact	Daily Production	Impact Factor	<sup>1</sup> Daily PM <sub>10</sub> Impact	ground PM <sub>10</sub> Level	³TOTAL PM₁₀ Level
Date	(tons)	(µg/m³ton)	(µg/m³)	(tons)	(µg/m³ton)	(µg/m <sup>3</sup> )	(tons)	(µg/m³ton)	(µg/m³)	(µg/m <sup>3</sup> )	(µg/m <sup>3</sup> )
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
		0.0628			0.0656			0.1662		20.00	
	a Daily DM In	0.0628			0.0656			0.1662		20.00	

Note 1: The Daily PM<sub>10</sub> Impact (μg/m³) for each plant is calculated by multiplying the Daily Production (tons) by the matching Ambient Impact Factor.

Note 2: Background PM<sub>10</sub> Level (µg/m<sup>3</sup>) is from Haul Roads and Stockpiles.

Note 3: The TOTAL PM<sub>10</sub> Level (μg/m³) is calculated by summing the Daily PM<sub>10</sub> Ambient Impact(s) and the Background PM<sub>10</sub> Level. A TOTAL PM<sub>10</sub> Level of less than 150 μg/m³ in any 24-hour period indicates compliance.

# Attachment AA: Best Management Practices (BMPs)- Construction Industry Fugitive Emissions

Construction Industry Sites covered by the Interim Relief Policy shall maintain Best Management Control Practices (BMPs) for fugitive emission areas at their installations when in operation. Options for BMPs are at least one of the following:

#### For Haul Roads:

#### Pavement of Road Surfaces –

- A. The operator(s) may pave all or any portion of the haul roads with materials such as asphalt, concrete, and/or other material(s) after receiving approval from the program. The pavement will be applied in accordance with industry standards for such pavement so as to achieve "Control of Fugitive Emissions" while the plant is operating.
- B. Maintenance and/or repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
- C. The operator(s) shall periodically water, wash and/or otherwise clean all of the paved portions of the haul road(s) as necessary to achieve control of fugitive emissions from these areas while the plant is operating.

#### 2. Usage of Chemical Dust Suppressants –

- A. The operator(s) shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to all the unpaved portions of the haul roads. The suppressant will be applied in accordance with the manufacturer's suggested application rate (if available) and re-applied as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
- B. The quantities of the chemical dust suppressant shall be applied, re-applied and/or maintained sufficient to achieve control of fugitive emissions from these areas while the plant is operating.
- C. The operator(s) shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

#### 3. <u>Usage of Documented Watering</u> –

- A. The operator(s) shall control the fugitive emissions from all the unpaved portions of the haul roads at the installation by consistently and correctly using the application of a water spray. Documented watering will be applied in accordance with a recommended application rate of 100 gallons per day per 1,000 square feet of unpaved/untreated surface area of haul roads as necessary to achieve control of fugitive emissions from these areas while the plant is operating. For example, the operator(s) shall calculate the total square feet of unpaved vehicle activity area requiring control on any particular day, divide that product by 1,000, and multiply the quotient by 100 gallons for that day.
- B. The operator(s) shall maintain a log that documents daily water applications. This log shall include, but is not limited to, date and volumes (e.g., number of tanker applications and/or total gallons used) of water application. The log shall also record rationale for not applying water on day(s) the plant is in operation (e.g., meteorological situations, precipitation events, freezing, etc.)
- C. Meteorological precipitation of any kind, (e.g. a quarter inch or more rainfall, sleet, snow, and/or freeze thaw conditions) which is sufficient in the amount or condition to achieve control of fugitive emissions from these areas while the plant is operating.
- D. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads. The operator(s) shall record a brief description of such events in the same log as the documented watering.
- E. The operator(s) shall record the date and the amount of water applied for each application on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

<sup>&</sup>lt;sup>1</sup> For purposes of this document, Control of Fugitive Emissions means to control particulate matter that is not collected by a capture system and visible emissions to the extent necessary to prevent violations of the air pollution law or regulation. (Note: control of visible emission is not the only factor to consider in protection of ambient air quality.)

#### For Vehicle Activity Areas around Open Storage Piles:

- 1. Pavement of Stockpile Vehicle Activity Surfaces -
  - A. The operator(s) may pave all or any portion of the vehicle activity areas around the storage piles with materials such as asphalt, concrete, and/or other material(s) after receiving approval from the program. The pavement will be applied in accordance with industry standards for such pavement so as to achieve control of fugitive emissions while the plant is operating.
  - B. Maintenance and/or repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
  - C. The operator(s) shall periodically water, wash and/or otherwise clean all of the paved portions of the vehicle activity areas around the storage piles as necessary to achieve control of fugitive emissions from these areas while the plant is operating.

#### 2. <u>Usage of Chemical Dust Suppressants</u> –

- A. The operator(s) shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to all the vehicle activity areas around the open storage piles. The suppressant will be applied in accordance with the manufacturer's suggested application rate (if available) and re-applied as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
- B. The quantities of the chemical dust suppressant shall be applied, re-applied and/or maintained sufficient to achieve control of fugitive emissions from these areas while the plant is operating.
- C. The operator(s) shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

#### 3. <u>Usage of Documented Watering</u> –

- A. The operator(s) shall control the fugitive emissions from all the vehicle activity areas around the storage piles at the installation by consistently and correctly using the application of a water spray. Documented watering will be applied in accordance with a recommended application rate of 100 gallons per day per 1,000 square feet of unpaved/untreated surface area of vehicle activity areas around the storage piles as necessary to achieve control of fugitive emissions from these areas while the plant is operating. (Refer to example for documented watering of haul roads.)
- B. The operator(s) shall maintain a log that documents daily water applications. This log shall include, but is not limited to, date and volumes (e.g., number of tanker applications and/or total gallons used) of water application. The log shall also record rationale for not applying water on day(s) the plant is in operations (e.g., meteorological situations, precipitation events, freezing, etc.)
- C. Meteorological precipitation of any kind, (e.g. a quarter inch or more rainfall, sleet, snow, and/or freeze thaw conditions) which is sufficient in the amount or condition to achieve control of fugitive emissions from these areas while the plant is operating.
- D. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads. The operator(s) shall record a brief description of such events in the same log as the documented watering.
- E. The operator(s) shall record the date and the amount of water applied for each application on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

Mr. Geoffrey Quo Vice President of Operations Materials Packaging Corporation P.O. Box B Harrisonville, MO 64071

RE: New Source Review Permit - Project Number: 2005-11-023

Dear Mr. Quo:

Enclosed with this letter is your New Source Review permit. Please review your permit carefully and note the special conditions, if any, and the requirements in your permit.

Operation in accordance with the conditions and requirements in your permit, the New Source Review application submitted for project 2005-11-023, and your amended operating permit, if required, is necessary for continued compliance. Please review your amended operating permit, as it will contain all applicable requirements for your concrete plant, including any special conditions from your New Source Review permit.

The section of the permit entitled "Technical Review of Application for Authority to Construct" should not be separated from the main portion of your permit. The entire permit must be retained in your files. The reverse side of your permit certificate has important information concerning standard permit conditions and your rights and obligations under the laws and regulations of the State of Missouri.

If you have any questions regarding this permit, please do not hesitate to contact me at (573) 751-4817, or you may write to the Department of Natural Resources' Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102. Thank you for your attention to this matter.

Sincerely,

AIR POLLUTION CONTROL PROGRAM

Kendall Hale, P.E. New Source Review Unit Chief

KH:jkl

Enclosures

c: Kansas City Regional Office PAMS File: 2005-11-023 Permit Number: